

The NLB Roto-Reel® 200 Rotating Hose Reel



A convenient control pendant allows for remote operation

The NLB Roto-Reel® 200 is a compact rotating hose reel that provides an efficient way to clean pipe. The pneumatically powered reel allows operators to easily feed high-pressure hose in and out of pipes at a rate of up to 40 feet per a minute (12 MPM), eliminating the physical strain of pulling hose under high-pressure. Additionally, not only does the Roto-Reel spool the hose, the reel also rotates 360° at 30 rpm, causing the nozzle to travel the inner diameter of the pipe. The rotation improves cleaning coverage, while also helping the nozzle navigate around tight bends and curves. When coupled with an NLB line mole nozzle, the NLB Roto-Reel® 200 is the ideal system for hard to clean pipes.

The Roto-Reel is rated for operating pressures up to 20,000 psi (1400 bar) and is capable of handling up to 200 ft. (61 m) of 1/2" (12.7 mm) diameter hose. Skid-mounted and trailer mounted systems are available.

Features include:

- ❑ Maximum operating pressure up to 20,000 psi (1400 bar).
- ❑ Feeds and retrieves hose at speeds up to 40 FPM (12 MPM) .
- ❑ Holds up to 200 ft. (61 M) of 1/2" (12.7 mm) diameter hose.
- ❑ Skid-mounted dimensions of 9' long x 5' wide x 5.5' tall (2.75 m x 1.53 m x 1.68 m) and weighs approx. 2,500 lbs. (1,134 kg).
- ❑ Automated system reduces cleaning time and operator fatigue.
- ❑ Full 360° rotation of nozzle inside inner diameter of pipes at a speed of 30 rpm.
- ❑ Comes standard with protective caging.
- ❑ Requires 80 psi at 100 CFM air.



**The Leader in High-Pressure
Water Jet Technology**

Headquarters

29830 Beck Road
Wixom, MI 48393-2824
(248) 624-5555
FAX: (248) 624-0908
<http://www.nlbcorp.com>

Regional Offices

■ 159 Harmony Road, Mickleton, NJ 08056
(856) 423-2211 FAX: (856) 423-0997

■ 201 S. 16th, La Porte, TX 77571
(281) 471-7761 FAX: (281) 471-8738

■ 14302 Highway 44 N., Gonzales, LA 70737
(225) 622-1666 FAX: (225) 622-7366

■ 1323 E. Hill St., Signal Hill, CA 90755
(562) 490-3277 FAX: (562) 733-0780